

CounterTop

EFT930S_{series}

Delivering the flexibility of a choice of rapid communication technologies with 32-bit ARM processing and cutting edge security, the Ingenico EFT930S series assures ultra fast yet highly cost-effective transactions – including debit, credit, reward and loyalty – that meet the needs of even the most demanding retail or banking environment. The EFT930S family's compact and space-saving design is packed with features – including integral smart card and long-swipe magnetic card readers, an ultra-fast ultra-quiet easy load printer, and backlit ergonomic keyboard – that combine to deliver intuitive and trouble free operations in any circumstance. This flexible and adaptable family offers a wealth of connectivity choice when it comes to communication. From POS integration, through to the peerless communication flexibility afforded by the EFT930S-EM and EFT930S-GEM combined-connectivity models, you're assured of the right solution for your business.

**ingenico**

EFT930S series

Security

The tamper resistant Ingenico EFT930S terminal series is universally EMV and PCI PED approved, delivering security-as-standard for consumer and merchant alike. A 32-bit RISC crypto-processor provides a uniquely scaleable and high-performance platform to support a host of new generation security applications, with no impact on transaction speed or reliability.

Performance

Utilizing ARM9 and ARM7 microprocessor technology, the robust yet powerful ET930S range of countertop terminals combine innovation and performance with multiple connectivity options – assuring a faster, more convenient and more reliable transaction every time.

Design/Ergonomics

Light enough to hand over for PIN entry, yet trim enough for even the smallest counter space, these neatly put together multi-application terminals are both versatile and user friendly. Clear white graphic displays, an easy to navigate keypad, and a high performance easy-load printer all add up to spectacular ‘zero delay’ customer service.

Communication

The EFT930S – which delivers serial link POS integration via a Magic Box – and EFT930L are both equipped with a V32bis modem for fast EMV authorization. Boost your connectivity with our dual-communication models; the EFT930S-EM offers dual Ethernet and fast modem anytime, the fully loaded EFT930S-GEM unites GPRS wireless, Ethernet and fast modem anywhere.

Software development

Ingenico delivers incremental revenue today and future proofs the terminal investments of tomorrow. Uniquely, the EFT930S series is backwards compatible with all 800+ Ingenico services and applications, while providing the rapid development environment on which to build a compelling portfolio of targeted, new generation services.

Field Services

To reduce total cost of ownership and enable banks and merchants to maximize their terminal investments, Ingenico provides a comprehensive range of terminal and software update and management services – both remotely and in the field. Fully certified professional and local language helpdesks operate in every territory to ensure Ingenico is on hand to support customers 24 hours a day, seven days a week, 365 days a year.



NAME		EFT930S-L	EFT930S	EFT930S-xxx
Processor	Type: ARM 9 & ARM 7	●	●	●
	Speed: 200 MIPS & 50 MIPS	●	●	●
Memory (RAM/Flash)	8MB/16MB	●		
	8MB or 16MB/16MB		●	●
Removable Memory	MMC/SD Card			optional
Communication Mode	Dial-up Modem	●	●	M
	Ethernet			E
	GPRS			G
SAM	1	●		●
	2		●	●
Card readers	Smart card	1	1	1
	Magstripe Track 1/2			●
	Track 1/2/3	●	●	●
Display	Graphic 128 x 64	●	●	●
	Backlit	●	●	●
	Yellow/Green	●	●	
	White			●
Keyboard	Number of keys	16	16	16
	Function/Navigation keys	6	6	6
	Backlit	●	●	●
Buzzer		●	●	●
Thermal Printer	Lines/second	18 lps	18 lps	18 lps
	RS232	2		
Connections on terminal	Mini USB Host		2	2
	Mini USB Slave		1	1
	Power supply connector	1	1	1
Power Supply	External Power supply: 100-240V 50-60 Hz	●	●	●
Magic Box			●	●
Connections on Magic Box	Power supply connector		1	1
	RS232		1	1
	Line in		1	1
	Phone out		1	
	Ethernet			1
Size (in mm)	Terminal: 79 x 180 x 65	●	●	●
	Paper Roll (width/Ø): 58/Ø40	●	●	●
Weight (in gr)	Terminal	410	410	410 to 460
	Lens	optional	optional	optional
	Printer cover flap	optional	optional	optional
Customization	Casing	optional	optional	optional
Environment	Operating temperature: +5°C to +45°C	●	●	●
	Storage temperature: -20°C to +55°C	●	●	●
	Relative humidity: 85% HR at +40°C	●	●	●
PCI PED	Online & offline	●	●	●

www.ingenico.com

