



HSM V-Press 840

The HSM V-Press 840 provides first-class results and delivers highly compressed bales, even with heavily expansive materials.

Product type description	HSM V-Press 840 plus	HSM V-Press 840 max
Order number	6147234	6147334
EAN Code	4026631030762	4026631030700
Pressing power	356 kN	356 kN
Specific pressing power	38.03 N/cm ²	38.03 N/cm ²
Press chamber depth	780 mm	780 mm
Loading height	1100 mm	1100 mm
Loading aperture width	1195 mm	1195 mm
Loading aperture height	650 mm	650 mm
Press chamber width	1195 mm	1195 mm
Bale length	1200,00 mm	1200,00 mm
Bale width	780 mm	780 mm
Bale height	1200 mm	1200 mm
Bale weight (max.)	360 kg	360 kg
Number of strappings	4	4
Strapping material	wire	wire
Cycle time in idle operation	32 s	32 s
Hourly bale output	2 - 3	2 - 3
Type of door	sliding door	sliding door
Door lock	handwheel	hydraulic
Driving power	7.5 kW	7.5 kW
Voltage	400 V	400 V
Frequency	50 Hz	50 Hz
Depth	1247 mm	1247 mm
Width	1767 mm	1767 mm
Height	2985 mm	2985 mm
Weight	1990 kg	2066 kg
Order no. tape/wire	6135993002	6135993002

Product type description	HSM V-Press 840 eco
Order number	6147134
EAN Code	
Pressing power	356 kN
Specific pressing power	38.03 N/cm ²
Press chamber depth	780 mm
Loading height	1100 mm
Loading aperture width	1195 mm
Loading aperture height	650 mm
Press chamber width	1195 mm
Bale length	1200 mm
Bale width	780 mm
Bale height	1200 mm
Bale weight (max.)	360 kg
Number of strappings	4
Strapping material	wire
Cycle time in idle operation	32 s
Hourly bale output	2 - 3
Type of door	double door
Door lock	handwheel
Driving power	7.5 kW
Voltage	400 V
Frequency	50 Hz
Depth	1069 mm
Width	1767 mm
Height	2985 mm
Weight	
Order no. tape/wire	6135993002