KX-ZB2
电脑数控扎钞机

凯勋 KaiXun

Computerized numerical control money binder

CE



❒ ISO9001:2000 国际质量体系认证

❒ Pass The Certification Of ISO9001:2000

概　述

本机实现了全自动快速纸带捆扎纸币，具有温度数字调节控制、捆扎位置可随意调节、掉电记忆、操作简单、捆扎美观结实、效率高、捆扎成本低的等特点。是金融部门和大商场用来捆扎纸币的理想机具。

OUTLINE

The machine can quickly bind the paper currency automatically with paper tapes, which has features such as temperature and digital adjustment and controlling, and free binding position adjustment, shut off memory, convenient operation, firm and solid, efficient and low cost binding, and is an ideal tool for financial sectors and large markets to bind the paper currency.

功能特点

❒ 全自动快速捆扎纸币。
❒ 微电脑控制，操作简单。
❒ 纸带捆扎可用按键随意调节。
❒ 纸带热压头温度实时显示，并且可用按键调节。
❒ 热压式纸带捆扎，使之美观、牢固。
❒ 故障自检并显示代码。

FEATURES

❒ Binding paper currency automatically and quickly
❒ Computer control and convenient operation
❒ Paper currency binding can be freely adjusted by button
❒ The paper tape hot press terminal has real time display
❒ It can be adjusted by botton.
❒ Self trouble testing and code display

技术参数

❒ 使用环境温度：0℃-40℃。
❒ 使用环境相对湿度：30%-80%。
❒ 使用电源：AC100V-240V ,50Hz/60Hz。
❒ 功　　率：最大55W，待机20W。
❒ 温度调节：105℃-140℃。
❒ 捆扎位置：35~85mm捆扎纸带中心点至纸币前边的距离。
❒ 适用纸带：本公司监制的DET20×180纸带。
❒ 扎钞速度：1.8秒/次。
❒ 重　　量：约6kg。
❒ 外形尺寸（长×宽×高）：280×198×215mm

SPECIFICATIONS

❒ Operation ambient temperature: 0℃ ~40℃
❒ Operation ambient relative humidity:30%~80%
❒ Operation ambient power supply: AC100V~240V , 50Hz/60Hz
❒ Power: Max:55w, inactive:20w
❒ Temperature adjustment: 105℃~140℃
❒ Binding position: 35~85mm, distance from the center of the binding paper currency to front edge of paper currency
❒ Applicable paper tapes: DET20×180 paper tape manuf actured under supervision of our company.
❒ Binding speed: 1.8s/bundle
❒ Weight: about 6kg
❒ Dimension(L×W×H): 280×198×215mm